

**DENSO ULTRAFLEX PSA 180 TAPE****DESCRIPTION**

A cold applied self adhesive tape based on low density polyethylene with a pressure sensitive adhesive. It is intended for use as an outerwrap over Denso petrolatum tapes or Densopol and Densoclad cold applied laminate tapes to enhance resistance to damage by backfill or soil stress and provide a clean neat outer surface.

PROPERTIES	TEST	TYPICAL DATA
Colour		Yellow or Black
Breaking Strength	ASTM D1000	31 N/cm
Elongation at Break	ASTM D1000	590%
Tear Strength	ASTM D1004	16 N
Adhesion To Steel To Self	ASTM D1000	6.5 N/cm 1.2 N/cm
Breakdown Voltage	Transco CW2	18 kV
Temperature Range For Application For Service		0°C to 45°C -20°C to 50°C
Thickness	ASTM D1000	0.18mm
Weight		0.17kg/m ²
Roll length		33 metres
Roll widths		50, 100, 150mm (or as ordered)
Core ID		76mm

Important

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9002 1994 (Certificate No. FM01548).

Winn & Coales (Denso) Ltd, Denso House, Chapel Road, London SE27 0TR, United Kingdom
Tel: +44 (0) 20 8670 7511 Fax: +44 (0)20 8761 2456 Email: mail@denso.net Website: www.denso.net