

Densostrip Primer

Bitumen primer for all surfaces prior to application of Densostrip

Composition

Densostrip Primer is a fast drying bitumen primer for all surfaces prior to the application of Densostrip flexible jointing compound.

Uses

Densostrip Primer is a primer for use with Densostrip on pre-cast concrete units.

Surface Preparation

Joint surfaces shall be undamaged, clean and dry. Wire brush to remove dust, dirt and loose material.

Application

See *Instructions for Use* for further details.

Apply one coat by brush.

Use white spirit for cleaning.

Application temperature: 0°C to +45°C.

Availability

5 L and 25 L drums

Storage Conditions

Store all components upright in original packaging in a cool, dry, area. Keep away from heat, sparks and open flames.

Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Typical Properties

Solids	64%
Flash Point	>23°C
Specific gravity	0.94
Drying time	10 – 20 minutes
Surface coverage	3-5 m ² /L.
VOC	<390 g/L

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).